

## STATIC ROPES

### SECURE STATIC ROPE II

#### STATIC ROPE | DIAMETER 11 MM

Static rope with diameter 11 mm, certified CE EN 1891.  
 Available in different lengths: 60, 100, 200m.  
 Durable and easy to handle, it is the perfect choice for work at height and professional applications.  
 Produced by Tendon, distributed in Italy by Kong.  
 For a complete overview of the full range please visit [www.mytendon.com](http://www.mytendon.com)

#### Recommended for

##### Professional: Work activities

Scaffolding and trestels, Metal structures, Confined spaces, Treeclimbing/arboriculture, Cableway evacuation, Sailboats, Roof and inclined planes, Rope Access, Ladders and elevating platforms

##### Professional: Rescue activities

Cableway evacuation, Firebrigades and civil protection



Articolo	CE EN	Type	Diameter (mm)	Length (m)	Colour	Material	Weight (g/m)	Number of falls	Sheath slippage	Elongation (%)	◆ (kN)
9L110E3S060	CE EN 1891/A	Static	11	60	Yellow		84.6	20	-	4.5	35
9L110E3S100	CE EN 1891/A	Static	11	100	Yellow		84.6	20	-	4.5	35
9L110E3S200	CE EN 1891/A	Static	11	200	Yellow		84.6	20	-	4.5	35