

ANCHORAGE

ARO SLING TUBULAR

POLYAMIDE WEBBING LOOPS

Polyamide sling perfect to make a stopover or to extend an anchor point. The product is supplied in different colors to suit lengths.

Custom lengths are also available upon request. Available in black.

Width of tape: 15 mm

Breaking strength: 23 kN

High quality product completely developed and produced in Italy.

Recommended for

Sport: Activities

Caving, Mountaineering, Climbing, Canyoning, Snow & ice



Professional: Work activities

Scaffolding and trestels, Roof and inclined planes

Professional: Rescue activities

Firebrigades and civil protection



Articolo	CE EN	Material	 (g)	 (kN)	Size	Colour	A (mm)	Hole diameter (mm)
271T030R0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	28	23	30	Red Black	30 cm	/
271T030N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	28	23	30	Black	30 cm	/
271T040N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	35	23	40	Black	40 cm	/
271T050N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	43	23	50	Black	50 cm	/
271T060G0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	45	23	60	Black Green	60 cm	/
271T060N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	45	23	60	Black	60 cm	/
271T080O0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	60	23	80	Black Orange	80 cm	/
271T080N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	60	23	80	Black	80 cm	/
271T120R0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	90	23	120	Red Black	120 cm	/
271T120N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	90	23	120	Black	120 cm	/
271T150Y0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	115	23	150	Black Yellow	150 cm	/
271T150N00K	CE EN 795/B CE EN 354 CE EN 566	Polyamide	115	23	150	Black	150 cm	/
271T180O0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	135	23	180	Black Orange	180 cm	/
271T180N0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	135	23	180	Black	180 cm	/
271T250R0KK	CE EN 795/B CE EN 354 CE EN 566	Polyamide	160	23	250	Red Black	250 cm	/