

DESCENDERS

KES 2

NEW

KES 2 - Kong Evacuation System

Evacuation system for one or more operators. The steering wheel allows a short lifting and/or the operator evacuation.

Load capacity: two people.

Device that allow the evacuation of one or more operator with a descent up to 300 meters from workstations at height (cranes, wind turbines, rigging frames, power lines...).

The device is equipped with a rope with a diameter of 9 mm type A and two connectors at the ends.

The innovative magnetic brake system allows to automatically modulate the speed of descent according to the applied load. The braking system does not wear mechanical parts nor the rope.

The slotted rope on both ends allows the evacuation of more operators in sequential way.

Available with pre-assembled 30, 50, 80 m rope; other lengths on request.

Descent at a controlled speed of ca. 0.8 m/sec.



Recommended for

Professional: Work activities

Scaffolding and trestels, Metal structures, Cableway evacuation, Roof and inclined planes, Rope Access

Articolo	CE EN	Material	▲ (g)	Colour	Main dimension (mm)	Minimum rope diameter (mm)	Maximum rope diameter (mm)
228020300KK	CE EN 341 CE EN 1496/B		5900	Black	/	9	9
228020500KK	CE EN 341 CE EN 1496/B		7100	Black	/	9	9
228020800KK	CE EN 341 CE EN 1496/B		9000	Black	/	9	9