

POSITIONING

STATIC ROPE LANYARD

NEW

NEW COMPACT AND ERGONOMIC TERMINALS | NFC READY

Semi-static lanyard with two loops for positioning and anchoring. Diameter 11mm.

New compact and ergonomic terminals with rubber protections and integrated NFC chip to ensure quick and safe identification of the serial number.

Protective sheath included on sizes from 1 to 5 m.

On request we provide different sizes with any kind of Kong connector together with the lanyard.

Recommended for

Professional: Work activities

Scaffolding and trestels, Metal structures, Roof and inclined planes



Articolo	Certification	◀▶ (kN)	Length (m)	⚖️ (g)	Rope diameter (mm)	Length regulator
278L00060KK	CE EN 354	25	0.6	105	11	No
278L00100KK	CE EN 354	25	1	135	11	No
278L00150KK	CE EN 354	25	1.5	172	11	No
278L00200KK	CE EN 354	25	2	210	11	No
278L00250KK	CE EN 354	25	2.5	248	11	No
278L00500KK	CE EN 354	25	5	440	11	No
278L01000KK	CE EN 354	25	10	820	11	No
278L01500KK	CE EN 354	25	15	1200	11	No
278L02000KK	CE EN 354	25	20	1580	11	No
278L02500KK	CE EN 354	25	25	1960	11	No